



MODEL	X	X/T	BRACKET	X	X/T	BRACKET	X	X/T	BRACKET	X	X/T	BRACKET	X	X/T	BRACKET	G	E
0204....15	77-160	X/4	2	162-225	X/6	3	227-300	X/8	4	302-375	X/10	5	377-420	X/12	6	20	16
0204....25	102-210	X/4	2	212-300	X/6	3	302-400	X/8	4	402-500	X/10	5	502-600	X/12	6	26.5	23
0204....40	132-270	X/4	2	272-390	X/6	3	392-520	X/8	4	522-600	X/10	5	/	/	/	35	33
0204....50	152-320	X/4	2	322-450	X/6	3	452-600	X/8	4	/	/	/	/	/	/	42	41
0204....65	202-400	X/4	2	402-550	X/6	3	552-600	X/8	4	/	/	/	/	/	/	52	52
0204....75	212-450	X/4	2	452-600	X/6	3	/	/	/	/	/	/	/	/	/	58	58
0204....100	260-550	X/4	2	552-600	X/6	3	/	/	/	/	/	/	/	/	/	75	71

	0204....15	0204....25	0204....40	0204....50	0204....65	0204....75	0204....100
SPESORE LAMIERA / METAL SHEET THICKNESS / DICKE DES BLECHS	0.5-0.9	0.9-1.7	1.7-2.8	2.8-3.8	3.8-4.9	4.9-6.0	6.0-8.0
LUNGHEZZE / LENGTHS / LÄNGEN MIN-MAX (X)	40-420	51-600	66-600	75-600	100-600	105-600	130-600
DIAMETRO ROTANTE / ROTATING DIAMETER / Ø BIEGEEINSATZ (D)	15	25	40	50	65	75	100
LARGHEZZA CORPO / BODY WIDTH / BREITE DES GRUNDKÖRPERS (SW)	44	59	84	106	131	149	178
DIST. MIN. ROTANTE-FRONT / DIST. MIN. ROTATING BODY-FRONT PART / ABSTAND MIN. DREHKÖRPER (SF)	9	14	26	30	39	44	60
DIST. ROTANTE-CHIAVETTA / DIST. ROTATING BODY - WEDGE / ABSTAND DREHKÖRPER (SK)	35	45	58	76	92	105	118
DIST. ROTANTE-BASE (SH) - DIST. BODY-ROTATING BODY / ABSTAND DREHKÖRPER-GRUNDKÖRPER	22	35	48	60	73	86	96
LARGHEZZA SUPPORTO (GL) / SUPPORT WIDTH / BREITE HALTER	28.6	38.1	50.8	63.5	76.2	88.9	116
INGOMBRO SUPPORTO (L) / HOLDER OVERALL / HÖHE HALTER	5.4	8.2	12	16.35	20	24	30
INGOMBRO (M) / HOLDER / HALTER	7.9	12.4	19.9	24.8	31.6	38	49.7
DIAMETRI FISSAGGI (H) / DIAMETERS OF THE FIXING / BEFESTIGUNGSDURCHMESSER	M6	M8	M10	M12	M16	M16	M20
POSIZIONE DEI FISSAGGI (E) / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	16	23	33	41	52	58	71

Può lavorare anche senza lubrificazione / It works also without lubrication / Es funktioniert auch ohne Schmierung / Il peut fonctionner sans lubrification

SPECIAL GEOMETRIES AND LENGTHS (600 mm+) AFTER CONSULTING NEWSTARK'S TECHNICAL DEPARTMENT

STANDARD MODEL ≥ 1M STROKES
ECO MODEL UP TO 500K STROKES

MODELLO D'ORDINE / ORDER EXAMPLE / BESTELLBEISPIEL / MODÈLE DE COMMANDE

STD MODEL	0204	TYPE BEND	03	Ø DIAMETER	Ø50	LENGHT	500	ANGLE	90°
ECO MODEL	E204	TYPE BEND	03	Ø DIAMETER	Ø50	LENGHT	500	ANGLE	90°